



#### **DEPARTMENT OF ENVIRONMENTAL SERVICES**

#### **MEMORANDUM**

TO: Oliver Orjiako

COPY: Jose Alvarez; Jen Langevin; Jeff Schnabel

FROM: Ron Wierenga

DATE: April 7, 2014

## **SUBJECT: VBLM assumptions for stormwater facilities**

I understand that a question was raised about new stormwater regulations at the March 19<sup>th</sup> work session with the Board on the Vacant Buildable Lands Model. Specifically, the assumptions for land dedicated to public infrastructure for commercial and residential development. A request was made that you look into how new regulations may affect the need for more land as a result of larger pond sizes.

Jose Alvarez asked me if I had made any projections of increased land needed to accommodate the new stormwater regulations. In this memo I respond to Jose's question and provide additional information for your consideration.

I have not made any projections about the need for more land to accommodate new stormwater regulations. I understand that on a single-project scale it seems intuitive that a bigger pond means less land. But I don't think anyone has considered the theory at a landscape level. With new regulations there's also there's an underlying assumptions people won't continue business as usual when it comes to project planning and design, thus changes to other requirements or planning tools should moderate impacts.

I'm not sure which 'new regulations' people were talking about at the work session so I'll briefly address both high and low flow standards. The 2007 municipal stormwater permit brought strict regulations for high flows by requiring developers to match historic pre-developed runoff rates. If a development is using detention to control flows then this will result in detention ponds getting much larger in difficult soils. Developments are typically using infiltration to a higher degree in well-drained soils so the impact is much less; particularly if we move toward letting them put it in the public right-of-way.

Clark County didn't start requiring the permit's high flow standard until December 2011, but the majority of cities and counties in the state made the standard effective in 2009. I haven't, over the past four years that most of Washington State has been using this standard, heard of agencies modifying buildable lands model assumptions or adding more land to offset land dedicated to storm facilities. Perhaps more cities and counties will make that argument as comprehensive plan updates come around, we'll see.

The other new regulations that people may be talking about are permit requirements to incorporate Low Impact Development practices into our stormwater code and design manual by July 2015. The net impact of this change will essentially be a decentralizing the storm system. Runoff will be dispersed and collected by smaller facilities spread throughout private and public property, including the public right-of-way. Our recent road standards update has opened up possibilities of using the public right-of-way for managing runoff and should save more land for development. There will still be a need for ponds on some sites to manage high flows but they should be smaller than without LID practices managing low flows.

I worked with Jen Langevin in Clean Water to research a basis for adding land to the public infrastructure assumption. When looking for specific examples of needing additional land for stormwater facilities and regulations, there are few. The Puget Sound Water Quality Management Plan is a comprehensive state and federal strategy to protect and restore the biological health and diversity of Puget Sound. Nowhere inside of it or the case study, Urban Stormwater Management: Lessons from Australia and the United States, is there mention of need for more land to improve storm water management. One study does conclude that limiting the impervious surface ratio can aggravate urban sprawl. They propose that in reality, developers may purchase more land to bring the ratio of impervious to pervious surfaces down. This is somewhat irrelevant for us because we do not impose impervious area limits on developments.

The urban fringe is especially vulnerable; due to the land costs. Surveys have shown that most suburban residents are willing to spend the extra money for a larger lot and larger home, and it does not seem to effect residents' decisions on spending more money to build houses in the impervious surface regulated areas (Sung et. Al, 2010). On the other hand, in the technical guide for low impact development for Puget Sound they cite properly designed and implemented applications can significantly reduce stormwater pond size requirements (Hinman, 2012). Therefore, using low impact development techniques can reduce developable land that is used for infrastructure. In support of this statement, the EPA's document on smart growth states that when smart growth strategies are employed, such as more compact development, they disturb less land and accommodate more development (EPA, 2006).

Turning to other municipalities in our area we can look at how they are planning for stormwater facilities in their own regions as a basis. In the King County buildable land report they are projecting 12% land for public facilities including; drainage facilities, parks, and schools. Snohomish County projects 5% land for stormwater use. They also state that there is no loss in achieved buildable densities from stormwater facilities. This is due to the flexibility of plat design and planning. The city of Pacific, located in Pierce County, is projecting an additional 0.19% land for stormwater facilities in the future. On the other hand, the city of Buckley, also located in Pierce County, plans for 20% land for stormwater use. Multnomah County estimates stormwater facilities impact on residential capacity is low, less than 15%. There is a varied range here but we can see these counties are at or below 20% and many of their estimates include other public facilities or infrastructures.

Lastly, I encourage you to take a look at the existing VBLM assumptions to benchmark where developments have fallen on the spectrum. Attached to his memo are some of the case studies where Henry Schattenkerk in Clean Water looked at how much land was dedicated to stormwater facilities, both on good and bad soils for infiltration. The numbers range from less

than 1% to 15% of the total land needed for storm infrastructure. You would have to combine this with the area needed for roads to benchmark these examples against the current model assumptions. But I'm sure GIS could do that for you on a fairly short turnaround.

#### **Attachment: Case Studies**

Following are some projects from the last few years with stormwater facility sizes compared to the overall project area. Average portion of the project area used for storm facilities for those listed below is about 7%.

Except for Dunning Meadows Subdivision and Erickson Farms FA3118, projects with stormwater facilities that were mostly or entirely underground were skipped. Examples of these include Chuck's Market, 139<sup>th</sup> Street Medical Plaza and Fairground Station. All three have parking lots built over most of the facility. So while the facility is significant in size, the developer can still utilize the surface area for other uses.

#### Cedar Crest Subdivision

Soils: moderately drained
Public FA3119, wet pond storm facility
ENG2006, construction Aug – Dec 2013
Development area 91,900 sq ft
Stormwater facility area 7,791 sq ft (8.5%)

## Erickson Farms Subdivisions

Soils: moderately drained

Public FAs 3001 (Wetpond) & 3118 (filter vault & underground detention)

FA3118 is entirely underground, but is also located on a separate tract of land dedicated as a storm facility

ENG2007, construction June 2012- October 2013

Development area 1,508,000 sq ft (so far two phases to these facilities)

Stormwater facilities total area 67,720 sq ft (4.49%)

#### The Hampton at Salmon Creek (commercial)

Soils: moderately to well drained.

Private FA3117, filter vault and detention pond.

ENG2012, construction Oct 2012 to Oct 2013.

Development area 116,800

Stormwater facility area 11,555 (9.9%)

#### Chinook Place Subdivision

Soils: moderately drained

Public FA3116, bioswale & detention pond.

ENG2006, construction July to November 2013.

Development area 203,500 sq ft

Stormwater facility area 11,230 sq ft (5.5%)

## Mount Vista Estates Phases 2 - 4 subdivision

Soils: poorly drained.

Public FA2993, bio-swale & detention pond.

ENG2006, construction July to November 2012.

Development area 491,270 sq ft

Stormwater facility area 29,150 sq ft (5.9%)

## Mount Vista Estates Phase 1 subdivision

Soils: poorly drained.

Public FA2847, bio-swale & detention pond.

ENG2011, construction Aug to Dec 2011.

Development area 188,100 sq ft

Stormwater facility area 28,000 sq ft (14.8%)

<u>Chase Bank at 63<sup>rd</sup> St & Andresen Rd</u> (commercial) Soils: well drained (north half) & poorly drained/wetland (south half)

Private FA2815, filter inlets and detention pond cells.

ENG2010, construction July to Nov 2010.

Development area 67,000 sq ft

Stormwater facility area 5,000 sq ft (7.4%)

## ------MORE-----

For comparison. Simply a selection of the latest projects we've added to the inventory regardless of soil type.

## Vista Dell Apartments (commercial)

Soils: Poorly Drained

Private FAs 3157, 3158 (infiltration trenches, bio-swales & detention pond, overflow to offsite

ENG2012, construction July 213 to March 2014

Project area: 237,524 sq ft

Stormwater facility area: 20,228 sq ft (8.5%)

#### S & R Floor Covering Warehouse (commercial)

Soils: Moderately Well Drained

Private FA3154 (filter strip / detention pond)

ENG2012, construction Jan 2013 to Feb 2014

Approx project site area: 14,000 sq ft

Stormwater facility area: 1792 sq ft (12.8%)

#### KWRL Bus Facility (commercial)

Soils: poorly drained

Private FA3153 (filter vault / detention pond)

ENG2013, construction Oct 2013 to Feb 2014

Project proposed total disturbed area: 264,000 sq ft

Stormwater facility area 31,163 sq ft (11.8%)

# Cascades Presbyterian Church Expansion (commercial)

Soils: excessively drained

Private FA3152 (filter inlet, infiltration trench)

ENG2013, construction July 2013 to Jan 2014

Project proposed disturbed area: 12,500 sq ft

Stormwater facility area: 600 sq ft (4.8%)

# Strawberry Hill II subdivision

Soils: moderately drained.

Public FA3134 (filter cartridge structure and infiltration trench bed)

ENG2008, construction July 2013 to Jan 2014.

Project area: 221,000 sq ft

Stormwater Facility area: 5,500 sq ft (2.5%)

# Norwegian Hollow subdivision

Soils: excessively drained

Public FA3129 (bio-retention facility)

ENG2013, construction Sept 2013 to Jan 2014

Project area: 648,200 sq ft

Stormwater Facility area: 6474 sq ft (1%)

# **Dunning Meadows subdivision**

Soils: excessively drained

Public FAs 3135 through 3147 (13 FAs, 16 filter inlets & trenches, all in dedicated ROW)

ENG2013, construction July 2013 to Jan 2014.

Project area: 860,000 sq ft

Approx area of stormwater facilities: 7,000 sq ft (0.8%)

Thom iGIS/Ken Pearrow
Road and Stormwater Right-of-Way Area

			Pero	Percent of Subdivision Area		
Residential Subdivisions	Total acres	ROW - Roads Acres	Road %	Stormwater %	Stormwater and Road Total %	
Cedar Crest	2.11	0.37365	17.71	8.5	26.21	
Erickson Farms	39.248	10.388	26.47	4.49	30.96	
Chinook Place	4.671	0.8728	18.69	5.5	24.19	
Mount Vista Estates Phases 2 - 4	11.278	1.4604	12.95	5.9	18.85	
Mount Vista Estates Phases 1	4.0667	0.74352	18.28	14.8	33.08	
Strawberry Hill 2	5.072	1.428	28.15	2.5	30.65	
Norwegian Hollow	14.8814 19.7575	3.10325 4.102	20.85 20.76		21.85 21.56	
Dunning Meadows						
Average	12.64	2.81	20.48	5.44	25.92	
Countywide	62,300.97	10,464.50	20.25			

			Prece	nt of Development Area	
Apartments	Total acres	ROW - Roads Acres	Road %	Stormwater %	Stormwater and Road Total %
Vista Dell Apartments	5.5	0.0491	0.893	8.5	9.4

			Precent of Development Area		
Commercial	Total acres	ROW - Roads Acres	Road %	Stormwater %	Stormwater and Road Total %
The Hampton at Salmon Creek	2.68	0	0	9.9	9.9
Chase Bank at 63rd St & Andresen Rd	1.603	0.0868	11.66	7.4	19.06
S & R Floor Covering Warehouse	Not in UGA				
KRWL Bus Facility	Not in UGA				
Cascades Presbyterian Church Expansion	Not in UGA				
Average	2.1415	0.0434	5.83	8.65	14.48

Road ROW analysis completed by GIS. Stormwater facilities analysis completed by Environmental Services.

28-Apr-14

## Orjiako, Oliver

From:

Mitch Kneipp <mkneipp@ci.washougal.wa.us>

Sent:

Thursday, March 27, 2014 4:10 PM

To:

Orjiako, Oliver

Cc:

Albrecht, Gary; Anderson, Colete

Subject:

FW: Stormwater Regulations

## Oliver,

Please see the response below from our consultant engineer regarding the area utilized for stormwater within Washougal.

Let me know if you have any questions.

#### Mitch

**Mitch Kneipp** | Community Development Director | City of Washougal City Hall | 1701 C Street | Washougal, WA 98671 | 360.835.8501 Ext.604 | FAX 360.835.8808

From: Wes Wegner [mailto:wes.wegner@wallisenq.net]

Sent: Thursday, March 27, 2014 4:02 PM

**To:** Mitch Kneipp; Jessica Herceg **Subject:** RE: Stormwater Regulations

#### Mitch,

In my opinion, 25% may be low if stormwater, street and other utilities are lumped together in the definition of "infrastructure" as used in your email. As you mentioned, infiltration rates in parts of Washougal allow stormwater facilities sizes to be minimized. This is not the case in many other areas in Clark County (and parts of Washougal). When infiltration is not feasible, large detention facilities are typically required which can take up a lot of space.

#### Example:

- 1. Myers Addition:
  - a. Total acreage of site = 3.5 acres
  - b. Road and stormwater infrastructure = Approximately 0.82 acres
  - c. Approximate Percentage = 23.4%
- 2. Ruby's Manor:
  - a. Total acreage of site = 3.91 acres
  - b. Road and stormwater infrastructure = 0.44 acres
  - c. Approximate Percentage = 11.2%
  - d. Notes: this development may not be representative. Large portions of the property are within Riparian Habitats and are not developable.

Addition is a fairly typical medium density subdivision. I can easily see the average being around 25% or higher ling on the density. Also, commercial/industrial developments often have stormwater requirements that require

additional treatment space and typically have larger impervious areas (resulting in larger storm facilities) due to the need for parking lots.

In summary, it is variable from site to site, but 25% would get the County close.

Hopefully this helps,

Wes Wegner, PE Project Engineer Direct: 360-852-9160 Office: 360-695-7041 wes.wegner@walliseng.net



From: Mitch Kneipp [mailto:mkneipp@ci.washouqal.wa.us]

Sent: Thursday, March 27, 2014 12:37 PM

**To:** Jessica Herceg; Wes Wegner **Subject:** Stormwater Regulations

#### Good Afternoon!

Clark County utilizes the Vacant Buildable Lands Model (VBLM) to analyze the potential for properties to develop or redevelop throughout Clark County and it's Cities. We utilize this tool to see if we have enough land available for each specific land use type (single-family, multifamily, commercial and industrial). Under this VBLM there are a lot of "assumptions" that are made. One of these assumptions is that approximately 25% of a property is used up with infrastructure including stormwater facilities. The question that Clark County has for us cities is; due to the new stormwater regulations should this percentage be upped? Because they did not adopt the new regulations they don't have any data to answer the question so they are urning to us.

ou guys have had a couple of pre-apps lately (which is awesome) so I was wondering if you ruld help me answer the County's question? Now I know each area and site are different, d we typically have pretty good infiltration here, but if you have any anecdotal information vould be great.

,,,,	 101	vou	time!

h

Mitch Kneipp | Community Development Director | City of Washougal City Hall | 1701 C Street | Washougal, WA 98671 | 360.835.8501 Ext.604 | FAX 360.835.8808